

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A hand tool comprising:
 - a body,
 - a motor contained within the body,
 - a void space between an internal surface of the body and at least a part of the motor,
 - a fluid inlet port provided in or on the body,
 - a fluid outlet port provided in or on the body,
 - ducting means which provides a channel for fluid supplied via the fluid inlet port through the void space and then on to the fluid outlet port,
 - said fluid outlet and inlet ports being connectable to fluid supply and fluid extraction conduits respectively,
 - ~~characterized in that~~ wherein a gaseous fluid is supplied to said fluid inlet from an external fluid source to cool the motor, and
 - a controller configured to turn off the motor ~~if the~~ in response to determining that a detected pressure of gaseous fluid exiting the void space ~~falls~~ has fallen below a predetermined level.
2. (Previously Presented) A hand tool as claimed in claim 1 wherein said supply conduit or extraction conduit are releasably attachable to said fluid inlet and said fluid outlet respectively.

3. (Previously Presented) A hand tool as claimed in claim 1 including a fluid transport means capable of providing fluid flow at a first pressure from said external fluid source through said void space via the supply conduit and egressing at a second pressure via the extraction conduit.
4. (Previously Presented) A hand tool as claimed in claim 1 wherein said motor is a brushless DC motor.
5. (Previously Presented) A hand tool as claimed in claim 3, wherein the controller is further employed to monitor the temperature of the hand tool or at least one component therein or the level of power supply or the pressure of fluid supply to the hand tool.
6. (Previously Presented) A hand tool as claimed in claim 1, wherein the controller includes motor diagnostic equipment.
7. (Previously Presented) A hand tool as claimed in claim 5 wherein said controller is capable of providing a signal to a computer monitoring system to indicate said temperature, level of power supply or the second pressure.
8. (Previously Presented) A hand tool as claimed in claim 7 wherein the computer monitoring system regulates the power supply or fluid supply if said controller indicates that the temperature, level of power supply or the second pressure is outside of predetermined limits.

9. (Previously Presented) A hand tool as claimed in claim 5 wherein said controller is capable of providing a signal to a visible indicator system to indicate the level of power supply or the second pressure.
10. (Previously Presented) A hand tool as claimed in claim 9 wherein the visible indicator system is capable of indicating if the temperature, level of power supply or the second pressure is outside of predetermined limits.
11. (Previously Presented) A hand tool as claimed in claim 1, wherein the controller is mounted remotely to the hand tool.
12. (Previously Presented) A hand tool as claimed in claim 1, wherein the controller includes an emergency power "off" or power disabling switch.
13. (Previously Presented) A hand tool as claimed in claim 1, wherein said controller controls power to the motor.
14. (Previously Presented) A hand tool as claimed in claim 1, wherein the motor is sealed within a motor housing, the void space existing between the internal surface of the body and at least a part of the motor housing.
15. (Canceled)

16. (Previously Presented) A hand tool as claimed in claim 1, wherein the fluid supplied to the void space is a compressed pneumatic fluid.

17. (Previously Presented) A hand tool as claimed in claim 1, wherein the fluid supplied to the void space is at a pressure greater than the external environment pressure.

18. (Previously Presented) A hand tool as claimed in claim 1, wherein the ducting means causes the fluid supplied to the fluid inlet port to, within the void space, first travel in a direction parallel to the axis of the body and motor housing and then to travel about the axis before again travelling along the axis to the fluid outlet port.

19. (Previously Presented) A hand tool as claimed in claim 1, wherein the fluid supplied to the void space maintains the motor temperature between about 35 °C to about 50 °C, or maintains the external temperature of the body between about 25 °C to about 40 °C.

20. (Previously Presented) A hand tool as claimed in claim 1, wherein the fluid supplied to the void space is provided at between about 15 L/min to about 35L/min, at between about 1.5 Bar to about 3.0 Bar, and at between about 8 °C to about 22 °C.

21. (Previously Presented) A hand tool as claimed in claim 1, wherein fluid is supplied to the void space only when the motor is operational.

22. (Previously Presented) A hand tool as claimed in claim 1, wherein the supply conduit also provides electrical power to the motor.

23. (Previously Presented) A hand tool as claimed in claim 1, wherein fluid is supplied to the void space only when the supply conduit is connected to the body.

24. (Previously Presented) A hand tool as claimed in claim 1, wherein said hand tool includes a power output means connected to the motor.

25. (Original) A hand tool as claimed in claim 24, wherein the power output means is a shaft capable of providing a driving force to a connected implement.

26. (Original) A hand tool as claimed in claim 25, wherein the implement may be an implement selected from one of the following types: a rotateable circular blade, a reciprocating blade, a pair of connected reciprocating blades, a rotating drum past a blade, a universal connection means able to attach or fit or house a tool.

27. (Previously Presented) A hand tool as claimed in claim 24, wherein the power output means comprises a rotating shaft, a toothed wheel or cog, disc or other suitable gear head.

28. (Previously Presented) A hand tool as claimed in claim 24, wherein the power output means includes a gearing system able to translate the power output by the shaft to a pre-determined speed or torque.

29. (Previously Presented) A hand tool as claimed in claim 1, wherein said hand tool includes a rotor position sensing means which outputs a signal which enables the position of the motor's rotor to be determined.

30. (Original) A hand tool as claimed in claim 29, wherein the rotor position sensing means comprises a Hall effect sensor.

31. (Previously Presented) A hand tool as claimed in claim 29, wherein energisation of the motor is determined at least in part on the basis of the rotor position signal.

32. (Previously Presented) A hand tool as claimed in claim 5, wherein the controller receives manual speed demand input and varies the output speed or torque of the motor accordingly.

33. (Previously Presented) A hand tool as claimed in claim 1, wherein a power switch handle is used to activate the hand tool.

34. (Original) A hand tool as claimed in claim 33, wherein activation is achieved by pushing a base of a plunger on the handle forward against a biasing force and enabling activation of a sensing switch.

35. (Previously Presented) A hand tool as claimed in claim 34, wherein activation of the switch is effected by movement of a bevelled surface of the plunger against

the switch and then by holding the handle down flush with the hand tool body.

36. (Previously Presented) A hand tool as claimed in claim 1, wherein a switch is provided for switching electrical supply to the motor on or off.

37. (Original) A hand tool as claimed in claim 36, wherein said switch is a non-contact magnetic reed switch located within the body which is sealed.

38. (Previously Presented) A hand tool as claimed in claim 1, wherein the hand tool includes a power input means adapted to be supplied with an input DC voltage via a connectable power cable.

39. (Original) A hand tool as claimed in claim 38, wherein the power input means comprises a quick-release plug or socket type arrangement.

40. (Previously Presented) A hand tool as claimed in claim 1, wherein the hand tool includes heat dissipation or insulation means.

41. (Original) A hand tool as claimed in claim 40, wherein the heat dissipation means are cooling fins.

42. (Previously Presented) A hand tool as claimed in claim 40, wherein the heat dissipation or insulation means substantially surrounds heat generating hand tool components and substantially reduces heat transfer from said hand tool body from

transferring heat to an operator.

43. (Previously Presented) A hand tool as claimed in claim 1, wherein the hand tool is constructed of metal, plastics or composite materials.

44. (Previously Presented) A hand tool as claimed in claim 1, wherein the body is sealed.

45. (Previously Presented) A hand tool as claimed in claim 1, wherein the body is substantially cylindrical in shape and sized to fit into a user's hand.

46. (Previously Presented) A hand tool as claimed in claim 1, wherein the motor housing and body are both substantially cylindrical in shape and are aligned coaxially with the void space existing over substantially all of the radially extending region between the motor housing and body.

47-48. (Cancelled)

49. (Previously Presented) The hand tool of claim 3, wherein the controller also monitors the second pressure via the extraction conduit.